## Royal Enfield Twin 12000 Mile Maintenance 12000 mile maintenance **GT/INT** 1 Change engine oil and filter, clean magnetic drain plugs 2 Inspect and adjust valve clearance In .08mm Ex .18mm 3 Replace spark plug 4 Inspect spark plug wires 5 Inspect rubber hose air filter to throttle body 6 Inspect rubber hose inlet manifold/adapter 7 Inspect rubber hose emission related components 8 Replace fuel filter 9 Replace air filter element 10 Inspect vent pipe under air filter box 11 Inspect secondary air hose 12 Adjust throttle cable free play 13 Adjust clutch cable freeplay 14 Lubricate hand lever pivot points 15 Inspect brake pads/Calipers Front and Rear 16 Replace brake fluid 17 Lubricate brake lever and gear shifter pivot points 18 Inspect brake lines/banjo bolt fittings 19 Inspect front forks for leakage 20 Inspect steering head movement 21 Clean lube and adjust rear drive chain 22 Inspect spoke tightness/rim runout 23 Clean and tighten battery terminal connections 24 Inspect tire condition/wear level 25 Lubricate side stand/center stand 26 Lubricate foot rest pivots 27 Inspect critical fasteners for tightness 28 Inspect ground terminals/tighten 29 Test ride

| Τ | hanl | k you f | from your | r Royal Enfield | Technician |  |
|---|------|---------|-----------|-----------------|------------|--|
|   |      |         |           |                 |            |  |