

Royal Enfield Twin 300 Mile Maintenance

300 mile maintenance		GT/INT
1	Change engine oil and filter, clean magnetic drain plugs	
2	Inspect and adjust valve clearance In .08mm Ex .18mm	
3	Inspect spark plug	
4	Inspect spark plug wires	
5	Inspect rubber hose air filter to throttle body	
6	Inspect rubber hose inlet manifold/adaptor	
7	Inspect rubber hose emission related components	
8	Clean air filter element	
9	Inspect vent pipe under air filter box	
10	Inspect secondary air hose	
11	Adjust throttle cable free play	
12	Adjust clutch cable freeplay	
13	Lubricate hand lever pivot points	
14	Inspect brake pads/Calipers Front and Rear	
15	Inspect brake fluid level/condition	
16	Lubricate brake lever and gear shifter pivot points	
17	Inspect brake lines/banjo bolt fittings	
18	Inspect front forks for leakage	
19	Inspect steering head movement	
20	Clean lube and adjust rear drive chain	
21	Inspect spoke tightness/rim runout	
22	Clean and tighten battery terminal connections	
23	Inspect tire condition/wear level	
24	Lubricate side stand/center stand	
25	Lubricate foot rest pivots	
26	Inspect critical fasteners for tightness	
27	Test ride	

Thank you from your Royal Enfield Technician _____