

Royal Enfield Twin 6000 Mile Maintenance

| 6000 mile maintenance | | GT/INT |
|-----------------------|---|--------|
| 1 | Change engine oil and filter, clean magnetic drain plugs | |
| 2 | Inspect and adjust valve clearance In .08mm Ex .18mm | |
| 3 | Inspect spark plug | |
| 4 | Inspect spark plug wires | |
| 5 | Inspect rubber hose air filter to throttle body | |
| 6 | Inspect rubber hose inlet manifold/adapter | |
| 7 | Inspect rubber hose emission related components | |
| 8 | Replace air filter element | |
| 9 | Inspect vent pipe under air filter box | |
| 10 | Inspect secondary air hose | |
| 11 | Adjust throttle cable free play | |
| 12 | Adjust clutch cable freeplay | |
| 13 | Lubricate hand lever pivot points | |
| 14 | Inspect brake pads/Calipers Front and Rear | |
| 15 | Inspect brake fluid level/condition | |
| 16 | Lubricate brake lever and gear shifter pivot points | |
| 17 | Inspect brake lines/banjo bolt fittings | |
| 18 | Inspect front forks for leakage | |
| 19 | Inspect steering head movement | |
| 20 | Clean lube and adjust rear drive chain | |
| 21 | Inspect spoke tightness/rim runout | |
| 22 | Clean and tighten battery terminal connections | |
| 23 | Inspect tire condition/wear level | |
| 24 | Lubricate side stand/center stand | |
| 25 | Lubricate foot rest pivots | |
| 26 | Inspect critical fasteners for tightness | |
| 27 | Inspect ground terminals/tighten | |
| 28 | Test ride | |

Thank you from your Royal Enfield Technician _____