

Royal Enfield 9000 Mile Maintenance

9000 mile maintenance		Himalayan
1	Inspect oil level	
2	Inspect and adjust Inlet / Exhaust tappet setting In. .08-.10mm Ex. .23-.25mm	
3	Inspect rubber components on intake	
4	Replace spark plug	
5	Inspect fuel hoses/injector connection for leaks	
6	Inspect fuel pump screws for tightness	
7	Inspect Coil wire	
8	Clean air filter element	
9	Inspect/adjust throttle/clutch cables	
10	Inspect clutch for slippage	
11	Inspect and adjust steering head bearings	
12	Inspect fork oil leakage	
13	Clean battery terminals and tighten battery and ground connections	
14	Inspect front and rear brake fluid	
15	Inspect front and rear brake pads	
16	Inspect hydraulic brake fittings, hoses, Calipers	
17	Inspect tires/adjust air pressure	
18	Check spoke tightness and wheel bearings	
19	Inspect and lube swingarm pivot bearings	
20	Inspect and lube/replace rear suspension linkages	
21	Clean and lube chain (every 600 miles or as needed)	
22	Inspect drive chain and sprockets	
23	Inspect rear wheel cush rubbers	
24	Inspect all critical fasteners	
25	Lube levers, side stand, footrest pivots (every 600 miles or as needed)	
26	Inspect/replace emission related components	
27	Test ride	

Thank you from your Royal Enfield Technician _____